Hot laminating

PLASTI 350 ASP DPG350ASPM

Automatic roll laminator with high pile suction feeder

Single or double side automatic laminator ideal for single side cover lamination and encapsulation with films from 25 to 250 microns.

Adjustable temperature of the rollers and speed will let you obtain a perfect laminating result depending on the film used.

Automatic high pile suction feeder with adjustable speed and delay will let you process any kind of glossy paper while perfectly adjust sheets overlapping for later precise trimming. Adjustable de-curling bar provides a flat results on single side laminations and the perforating device installed on top of upper lamination roll allow an easy and clean manual separation of single side laminated sheets.

The optional bursting unit can be installed in order to make this process even more automatic and more time efficient up to a production of 270 sheets (DIN A3) per hour.

Specifications:

- Max working width (mm): 340
- Max paper width (mm): 350
- Max paper thickness (gsm): 350
- Film thickness (um): 25-250
- Max temperature: 170° C
- Independent lower roller heating system can be switched off in order to allow single side (upper) hot lamination
- Rollers diameter: 45mm
- Control panel with preset function
- Roller pressure adjustment: manual
- Power consumption (VV): 1100
- Power requirements (V Hz): 230 50/60

Dimensions And Weight

- Dimension (mm): 730x750x1420
- Weight (Kg): 62

OPTIONAL

Tear off separation system

Modular tear off separator machine to combine with the Plasti 350 machine.

This system allows an accurate sheet separation that must be single-side laminated.


The laminating process becomes fully automated

Specifications:

- Maximum paper width: 350 mm
- Traction rollers width: 35 cm
- Double separator roller
- Operation is restriction-free paper length
- Delivery tray
- User-friendly paper length setting
- Electric PCB with motor protection system
- Power requirements: 230V
- Power consumption: 50W

Dimensions and Weight:

- LxPxH 472x300x416mm
- Weight: 25kg



12 cm high pile feeder



Anti curling device



